


Model 70 Differential pH Sensor

Features

- Differential Electrode Measurement Technique using Three Electrodes
- Replaceable Equitransferant Salt Bridge and Reference Reservoir
- Patented*, Non-fouling, Porous Teflon®* Liquid Junction
- Non-metallic Solution Ground for enhanced Chemical Resistivity
- Cable with Built-in Encapsulated Preamplifier
- Capillary Temperature Sensor for Quick Response
- TOP68 Connector allows easy sensor removal
- Glass reinforced Ryton® Body
- Versatile Body Style with 1-inch NPT Threads on both ends.
- Various Hardware available for Mounting Options
- Options Available for use with most Manufacturers Analyzers



Applications

- Water and Wastewater Treatment
- Coagulation and Flocculation
- Process Monitoring and Control
- Acid and Caustic Neutralization
- Plant Effluent
- Pulp Stock Batches
- Ore Separation
- Cooling Towers
- Plating Baths
- Separation Systems
- Boiler Flue Gas Scrubbers
- Textile Dye Processes
- General Industrial Service

Description

The Model 70 uses the field proven, three-electrode differential measurement technique; the pH and reference electrodes are compared to a ground electrode for excellent measurement accuracy, even in harsh chemical applications. The sensor body is offered in glass-reinforced Ryton for chemical compatibility in most process liquid solutions. The replaceable salt bridge and refillable reference reservoir insures a long service life in applications containing sulfides (H₂S) and metals such as lead, mercury, and silver. It will maintain a constant reference cell potential by resisting dilution over time with pressure and temperature changes. The patented porous Teflon reference junction resists fouling and chemical attack.

The sensor cable has a built-in preamplifier to boost the pH signal while ensuring a quiet and reliable measurement. The transmitter powers the preamplifier. A self-powered preamplifier is also available as an option for use with analyzers which do not have an adequate voltage source. The capillary temperature sensor design places the temperature element behind the pH sensitive membrane for accurate temperature measurement and compensation.

The 1-inch NPT versatile body allows mounting into a standard 1-inch pipe tee, onto the end of a pipe for immersion into a vessel and into an adapter pipe for mounting with 1-1/2 inch pipe tee. Mounting adapters are available in CPVC or 316 SS for direct replacement of GLI sensors used in 1-1/2 inch threaded pipe tees. Other materials are available upon request.

Specifications

Model 70	Specifications
Body Material	Ryton
O-rings	Viton
Measuring Range	0-14 pH
Operating Temperature Range	-5 to 95°C
Temperature Element	300 ohm NTC; PT100 and PT1000 also available
Pressure Range	100 psi @ 95°C
Maximum Flow Rate	Not flow sensitive
Sensitivity	Less than 0.005 pH
Stability	0.03 pH per 24 hours, non-cumulative
Sensor Cable (Detachable from Sensor)	6 conductor (3 twisted pair each pair shielded with a common drain wire), overall Mylar shield with drain wire, UV enhanced Santoprene jacket; rated to 135C. Encapsulated differential amplifier built into cable.

*United States Patent No. 4,128,468

®Teflon is a registered trademark of E.I. Du Pont de Nemours + Co.

®Ryton is a registered trademark of Phillips 66 Co.

Model 70 Differential pH Sensor

Ordering Information

Ordering Code	Description
M-70	Differential pH sensor with 300 ohm NTC and TOP68 connector.
Z7075	TOP68 Cable with transmitter powered preamplifier, 20 ft (6.0M) (for use with transmitters 6-20V)
Standard Options	
PT100	PT100 temperature compensation
PT1000	PT1000 temperature compensation
ORP	Platinum ORP electrode
Other Available Options	
3KTC	3 Kohm temperature compensation

Accessories

Part Number	Description
Z8160	CPVC adapter; 1 1/2 inch MNPT x 1 inch FNPT
Z8161	316 SS adapter; 1 1/2 inch MNPT x 1 inch FNPT
Z6000	Replacement salt bridge
Z7307	Replacement reference solution, 500 mls
	TOP68 Cable with self-powered preamplifier, 20 ft (6.0M)
	TOP68 Cable with self-powered preamplifier, 30 ft (9.1M)
	TOP68 Cable with transmitter powered preamplifier, 30 ft (9.1M)

Wiring Information

Measurement	Wire Color
pH electrode	Red
Reference Electrode	Green
Shield (both inner and outer shield)	Clear with Black Band
Temperature	Black
Temperature	Yellow
Supply Power for transmitter powered preamplifiers (+ terminal) -V to +V = 6 to 20V	White
Power (- terminal)	Blue

